

Dunlop Grout Sealer

Chemwatch Material Safety Data Sheet (REVIEW)
Issue Date: 15-Oct-2010
C477LP

Hazard Alert Code: NIL

CHEMWATCH 4661-41
Version No:3.1.1.1
Page 1 of 9

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

Dunlop Grout Sealer

STATEMENT OF HAZARDOUS NATURE

Not considered a Hazardous Substance according to the criteria of the New Zealand Hazardous Substances New Organisms legislation. Not regulated for transport of Dangerous Goods.

OTHER NAMES

"grout sealer"

PRODUCT USE


As cement based grout sealer.

SUPPLIER

Company: Ardex NZ Pty Ltd
Address:
32 Lane Street
Woolston
Christchurch,
New Zealand
Telephone: +64 3384 3029
Emergency Tel: **1800 222 841 (General Information)**
Fax: +64 3384 9779

Section 2 - HAZARDS IDENTIFICATION

CHEMWATCH HAZARD RATINGS



EMERGENCY OVERVIEW

Not hazardous

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
acrylic urethane resin	16889-77-3	10-60
bacteriacide		0-1
water	7732-18-5	30-60

continued...

Dunlop Grout Sealer

Hazard Alert Code: NIL

Chemwatch Material Safety Data Sheet (REVIEW)

Issue Date: 15-Oct-2010

C477LP

CHEMWATCH 4661-41

Version No:3.1.1.1

Page 2 of 9

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

Section 4 - FIRST AID MEASURES

NEW ZEALAND POISONS INFORMATION CENTRE 0800 POISON (0800 764 766)

NZ EMERGENCY SERVICES: 111

SWALLOWED

- Immediately give a glass of water.
- First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

EYE

- If this product comes in contact with eyes:
 - Wash out immediately with water.
 - If irritation continues, seek medical attention.
 - Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

- If skin or hair contact occurs:
 - Flush skin and hair with running water (and soap if available).
 - Seek medical attention in event of irritation.

INHALED

- If fumes, aerosols or combustion products are inhaled remove from contaminated area.
- Other measures are usually unnecessary.

NOTES TO PHYSICIAN

Treat symptomatically.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves in the event of a fire.
- Prevent, by any means available, spillage from entering drains or water courses.
- Use fire fighting procedures suitable for surrounding area.
- DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.
- Equipment should be thoroughly decontaminated after use.

FIRE/EXPLOSION HAZARD

- Non combustible.
- Not considered to be a significant fire risk.
- Expansion or decomposition on heating may lead to violent rupture of containers.
- Decomposes on heating and may produce toxic/ irritating fumes.
- May emit acrid smoke.

continued...

Dunlop Grout Sealer

Hazard Alert Code: NIL

Chemwatch Material Safety Data Sheet (REVIEW)

Issue Date: 15-Oct-2010

C477LP

CHEMWATCH 4661-41

Version No:3.1.1.1

Page 3 of 9

Section 5 - FIRE FIGHTING MEASURES

FIRE INCOMPATIBILITY

- None known.

Section 6 - ACCIDENTAL RELEASE MEASURES

MINOR SPILLS

- Clean up all spills immediately.
- Avoid contact with skin and eyes.
- Wear impervious gloves and safety goggles.
- Trowel up/scrape up.
- Place spilled material in clean, dry, sealed container.
- Flush spill area with water.

MAJOR SPILLS

Minor hazard.

- Clear area of personnel.
- Alert Fire Brigade and tell them location and nature of hazard.
- Control personal contact with the substance, by using protective equipment as required.
- Prevent spillage from entering drains or water ways.
- Contain spill with sand, earth or vermiculite.
- Collect recoverable product into labelled containers for recycling.
- Absorb remaining product with sand, earth or vermiculite and place in appropriate containers for disposal.
- Wash area and prevent runoff into drains or waterways.
- If contamination of drains or waterways occurs, advise emergency services.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Limit all unnecessary personal contact.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately.
- Use good occupational work practice.
- Observe manufacturer's storage and handling recommendations contained within this MSDS.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

SUITABLE CONTAINER

- Polyethylene or polypropylene container.
- Packing as recommended by manufacturer.
- Check all containers are clearly labelled and free from leaks.

continued...

Dunlop Grout Sealer

Hazard Alert Code: NIL

Chemwatch Material Safety Data Sheet (REVIEW)

Issue Date: 15-Oct-2010

C477LP

CHEMWATCH 4661-41

Version No:3.1.1.1

Page 4 of 9

Section 7 - HANDLING AND STORAGE

STORAGE INCOMPATIBILITY

Avoid contamination of water, foodstuffs, feed or seed.

None known.

STORAGE REQUIREMENTS

- Store in original containers.
- Keep containers securely sealed.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storage and handling recommendations contained within this MSDS.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



+



+



+



+



X



+

+: *May be stored together*

O: *May be stored together with specific preventions*

X: *Must not be stored together*

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

The following materials had no OELs on our records

- acrylic urethane resin:
- water:

CAS:16889- 77- 3

CAS:7732- 18- 5

MATERIAL DATA

ACRYLIC URETHANE RESIN:

WATER:

No exposure limits set by NOHSC or ACGIH.

DUNLOP GROUT SEALER:

Not available

PERSONAL PROTECTION



continued...

Dunlop Grout Sealer

Hazard Alert Code: NIL

Chemwatch Material Safety Data Sheet (REVIEW)

Issue Date: 15-Oct-2010

C477LP

CHEMWATCH 4661-41

Version No:3.1.1.1

Page 5 of 9

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EYE

- Safety glasses with side shields
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent].

HANDS/FEET

- Wear general protective gloves, eg. light weight rubber gloves.

OTHER

- No special equipment needed when handling small quantities.

OTHERWISE:

- Overalls.
- Barrier cream.
- Eyewash unit.

RESPIRATOR

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required. For further information consult site specific CHEMWATCH data (if available), or your Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

- Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.

Employers may need to use multiple types of controls to prevent employee overexposure.

General exhaust is adequate under normal operating conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Paste; mixes with water.

PHYSICAL PROPERTIES

Mixes with water.

continued...

Dunlop Grout Sealer

Hazard Alert Code: NIL

Chemwatch Material Safety Data Sheet (REVIEW)

Issue Date: 15-Oct-2010

C477LP

CHEMWATCH 4661-41

Version No:3.1.1.1

Page 6 of 9

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

State	Non Slump Paste	Molecular Weight	Not Applicable
Melting Range (°C)	Not Available	Viscosity	Not Available
Boiling Range (°C)	Not Available	Solubility in water (g/L)	Miscible
Flash Point (°C)	Not Available	pH (1% solution)	Not Available
Decomposition Temp (°C)	Not Available	pH (as supplied)	Not Available
Autoignition Temp (°C)	Not Available	Vapour Pressure (kPa)	Not Available
Upper Explosive Limit (%)	Not Available	Specific Gravity (water=1)	Not Available
Lower Explosive Limit (%)	Not Available	Relative Vapour Density (air=1)	Not Available
Volatile Component (%vol)	Not Available	Evaporation Rate	Not Available

Section 10 - CHEMICAL STABILITY

CONDITIONS CONTRIBUTING TO INSTABILITY

■ Product is considered stable and hazardous polymerisation will not occur.

For incompatible materials - refer to Section 7 - Handling and Storage.

Section 11 - TOXICOLOGICAL INFORMATION

Health hazard summary table:

Acute toxicity	Not applicable
Skin corrosion/irritation	Not applicable
Serious eye damage/irritation	Not applicable
Respiratory or skin sensitization	Not applicable
Germ cell mutagenicity	Not applicable
Carcinogenicity	Not applicable
Reproductive toxicity	Not applicable
STOT- single exposure	Not applicable
STOT- repeated exposure	Not applicable
Aspiration hazard	Not applicable

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

■ The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. The material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (eg. liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern.

EYE

■ Although the material is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).

continued...

Dunlop Grout Sealer

Hazard Alert Code: NIL

Chemwatch Material Safety Data Sheet (REVIEW)

Issue Date: 15-Oct-2010

C477LP

CHEMWATCH 4661-41

Version No:3.1.1.1

Page 7 of 9

Section 11 - TOXICOLOGICAL INFORMATION

SKIN

■ The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.

INHALED

■ The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.

CHRONIC HEALTH EFFECTS

Long-term exposure to the product is not thought to produce chronic effects adverse to the health (as classified by EC Directives using animal models); nevertheless exposure by all routes should be minimised as a matter of course.

TOXICITY AND IRRITATION

WATER:

ACRYLIC URETHANE RESIN:

■ No significant acute toxicological data identified in literature search.

DUNLOP GROUT SEALER:

■ Not available. Refer to individual constituents.

Section 12 - ECOLOGICAL INFORMATION

No data

Ecotoxicity

Ingredient	Persistence: Water/Soil	Persistence: Air	Bioaccumulation	Mobility
acrylic urethane resin	No Data Available	No Data Available	No Data Available	No Data Available

Section 13 - DISPOSAL CONSIDERATIONS

- Recycle wherever possible or consult manufacturer for recycling options.
 - Consult State Land Waste Management Authority for disposal.
 - Bury residue in an authorised landfill.
 - Recycle containers if possible, or dispose of in an authorised landfill.
- Insure that the disposal of material is carried out in accordance with Hazardous Substances (Disposal) Regulations 2001.*

continued...

Dunlop Grout Sealer

Chemwatch Material Safety Data Sheet (REVIEW)

Issue Date: 15-Oct-2010

C477LP

Hazard Alert Code: NIL

CHEMWATCH 4661-41

Version No:3.1.1.1

Page 8 of 9

Section 14 - TRANSPORTATION INFORMATION

HAZCHEM:

None

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS: UN, IATA, IMDG

Section 15 - REGULATORY INFORMATION

REGULATIONS

Regulations for ingredients

water (CAS: 7732-18-5) is found on the following regulatory lists;

"IMO IBC Code Chapter 18: List of products to which the Code does not apply", "International Fragrance Association (IFRA) Survey: Transparency List", "New Zealand Inventory of Chemicals (NZIoC)", "OECD List of High Production Volume (HPV) Chemicals", "OSPAR National List of Candidates for Substitution – Norway"

No data for Dunlop Grout Sealer (CW: 4661-41)

No data for acrylic urethane resin (CAS: , 16889-77-3)

Specific advice on controls required for materials used in New Zealand can be found at www.epa.govt.nz/search-databases/Pages/controls-search.aspx

Section 16 - OTHER INFORMATION

NEW ZEALAND POISONS INFORMATION CENTRE

0800 POISON (0800 764 766)

NZ EMERGENCY SERVICES: 111

EXPOSURE STANDARD FOR MIXTURES

■ "Worst Case" computer-aided prediction of spray/ mist or fume/ dust components and concentration:

■ Composite Exposure Standard for Mixture (TWA) :100 mg/m³.

■ Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net/references.

■ The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

continued...

Dunlop Grout Sealer

Hazard Alert Code: NIL

Chemwatch Material Safety Data Sheet (REVIEW)

Issue Date: 15-Oct-2010

C477LP

CHEMWATCH 4661-41

Version No:3.1.1.1

Page 9 of 9

Section 16 - OTHER INFORMATION

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: 15-Oct-2010

Print Date: 17-Dec-2012