



PRIMER & ADDITIVE



DUNLOP® PRIMER AND ADDITIVE is a ready to use primer for porous surfaces, wallboard and timber, prior to using **DUNLOP® UNDERTILE WATERPROOFING** and **DUNLOP® TILE ADHESIVES**.

DUNLOP® PRIMER AND ADDITIVE enhances the bond between the surfaces and the waterproofing or adhesives.

As an additive to grout, **DUNLOP® PRIMER AND ADDITIVE** enhances the colour of the grout, increases adhesion, resists abrasion and stains and imparts a degree of flexibility.

SURFACE PREPARATION

Clean surfaces to be primed, ensuring they are dry and free from dust.

COVERAGE

Varies depending on substrate and use (see below).

USES & APPLICATION

Pre-waterproof Priming

Designed to seal the substrate and enhance the adhesion qualities of **DUNLOP® UNDERTILE WATERPROOFING**. Use a sponge, brush, roller or spray to apply coating, ensuring the entire surface is sealed with the product. Drying time depends upon conditions, approximately 15-30 mins. Coverage is approximately 4m² per litre.

Prior to Adhering Tile Adhesives to Substrates

Enhances the adhesion of **DUNLOP®** tile adhesives to a diverse range of substrates e.g. fibre-cement sheets and concrete. Some very porous substrates may need 2 coats of primer e.g. AAC concrete. Use a brush or roller to ensure surface is sealed completely. Coverage is approximately 4m² per litre.

As a Grout Additive

Dilute 1:1 with clean water, or use undiluted when grouting over timber floors. When mixed with **DUNLOP® GROUT**, it will enhance the colour of the grout, impart a degree of flexibility and reduce porosity and staining. Add the grout to the liquid in a clean container stirring continually to achieve a lump free paste. The mix is then ready to apply to joints. In swimming pool applications, use a white **DUNLOP® COLOURED GROUT** (i.e. Polar White) mixed with undiluted **DUNLOP® PRIMER AND ADDITIVE**. The chemical balance of swimming pools must be maintained.

Wall Board Primer

Mix 1 part to 4 parts clean drinkable water. Apply to fibre-cement sheets with a brush or roller. Allow primer to dry for approximately 15 minutes prior to tiling. Coverage is approximately 8m² per litre of diluted mixture.

Timber Floor Primer

Use **DUNLOP® PRIMER AND ADDITIVE** undiluted. Apply to clean timber floors with brush or paint roller. Allow primer to dry for approximately 30 mins before tiling. Coverage is approximately 4m² per litre.

SHELF LIFE

DUNLOP® PRIMER AND ADDITIVE has a shelf life of 12 months when stored in the original unopened packaging, in a dry place at 30°C and 50% relative humidity.

PACKAGING

1L, 4L

DUNLOP GUARANTEE

Product is guaranteed for 10 years when installed to manufacturers instructions. Manufactured under a quality system certified as complying with ISO 9001 by an accredited certification body. Material Safety Data Sheets are available upon request.

TECHNICAL DATA

Characteristics of product:

Colour:	White
Bulk Density:	0.95g/cm ³ (loose)
Specific Gravity:	1.02± 0.01 kg/litre
pH:	8-9

Application Properties (at 23°C and 50% relative humidity)

As Primer

Drying Time:	15-30 mins (approx)
Coverage:	approx 8m ² per litre diluted approx 4m ² per litre undiluted

As Grout Additive

Refer to **DUNLOP® GROUT** packaging

As Adhesive Additive

Refer to **DUNLOP® ADHESIVE** packaging

USER NOTES

The technical details and recommendations contained in this data sheet are given in good faith and represent the best of our knowledge and experience at the time of printing. It is the responsibility of the user to ensure that the products are used in accordance with **DUNLOP** product instructions and in applications for which they are intended.

Exceeds Australian Standard AS 4992.1

DUNLOP is a trademark of Ansell Limited and is used under licence by **ARDEX** in Australia and New Zealand.

ARDEX AUSTRALIA PTY LTD. ABN 82 000 550 005
20 Powers Road, Seven Hills NSW 2147 Australia

ARDEX Australia Pty Ltd

NSW	Ph (02)9851 9100	Fax (02)9838 7970
VIC	Ph (03)9308 9255	Fax (03)9308 9332
QLD	Ph (07)3817 6000	Fax (03)3881 3188
SA	Ph (08)8268 2511	Fax (08)8345 3207
WA	Ph (08)9455 1644	Fax (08)9455 1227

ARDEX New Zealand Ltd

Auckland	Ph (09)5800 005	Fax (09)5799 963
Wellington	Ph (04)5685 949	Fax (04)5686 376
Christchurch	Ph (03)3843 029	Fax (03)3849 779

PAA-12/06_v3

TOLL FREE SERVICE:
1800 222 841(Aust) 0800 224 070 (NZ)

www.dunlopdiiy.com